



Replacement  
Battery



USB Cable



TCP/IP



EM Card  
Password



Card Capacity	10.000
Password Capacity	3.000
Recording Capacity	100.000
Card Reader	Proximity (Opsiyonel Mifare)
Display	24 inç
Communication	TCP/IP, USB/Kablo, RS485
USB Reader	Supports
Additional Feature	Perception
Audio Output	Buzzer
RTC	Supports
Operating Voltage	DC 9V
Working in Humid Environment	20% - 60%
Operating Temperature	0°C - 50°C
Working Mode	Standalone / Master / Read Mode
Description Mod	ID Card, Password
Display Language	Turkish and Multi - Language support

Access Control	Direct door lock control / Door lock control with Wiegand access control / Defining 50 different time intervals / Combination Identification / Anti-pass back
Multi-Door Control	Supports
Alarm Feature	Forgery / Long time open door / illegal door opening and alarm
Power Management	Sleep mode supported
Self Test	Supports
FAR/FRR	0.0001(%)
Recognition Speed	<1.0 seconds
Smart Adaptation Feature	Supports
Working Method	Online
Idle Current	400 mA



www.flytek.com.tr

**Flytek Ltd. Şti.**  
8756 St. No:60 D.1/B Yenimahalle  
Çiğli/İzmir

+90 232 423 43 59  
+90 536 740 30 69  
sales@flytek.com.tr