



General Features

Operation

Controlled or control-free entrance/exit in both directions.

Chassis

AISI 304 quality stainless steel. Optional: Black stainless steel.

Wing

None

Upper Table

10 mm black tempered glass. Optional: Wood.

Functions

Operation in either directions with microprocessor control and ability to detect side by side, successive and opposite passes thanks to upper level sensors, audio/silent alarm. Memory feature ensures that authorizations during passes are kept in memory, resulting in very fast entry and exit.

Mechanism

None

Sensors

10 reciprocal sensors in every corridor. Optional: 16 reciprocal sensors.

Emergency Mode

Turnstile switches to emergency mode upon the receipt of a signal from fire detection system and passes in both directions become possible.

Safety Level Setting

With 4 security levels that can be defined as desired by the customer, turnstile is able to detect unauthorized passes and passes in the opposite direction and prevents or notifies, with audio or discreetly.

Indicator

Led lighting around the top plate and transition leds.

Operating Voltage	100-230 VAC. 47-60 Hz
Power Consumption	15W
Operating Temperature	0° / +70°
Passage Speed	60 persons / minute
Passage Width	50-150 cm
Weight	~47 Kg (Single Wing)
Security Level	Deterrent
Areas of Use	Suitable for indoor use
Accessories	Remote control unit. Stainless steel reader apparatus. Meter. Button control unit. Stainless steel reader leg. Stainless steel bottom plate.

