



Features

Device Features

PowerGuard high-sensitivity door type metal detector, independent LED light bars lined up along the door indicate the position of the threatening object on the person passing by. This detector has 6 detection zones and there is no dead zone. In general, there are 100 steps of sensitivity adjustment and these 6 zones have sensitivity settings between 0-99 separately. The electronic unit is protected against external factors in the locked compartment on the detector. PowerGuard products are CE and ISO 9001:2008 certified.

Dimensions	930 (Width)30mm (Depth) 22300mm (Height)
Operating Temperature	-20°C / +50°C 95% RH
Strength	15 W
Net Weight	85 kg
Alarm	Audio and Visual
Sensibility	100 Steps of general sensitivity adjustment 0-99% step of the zones separately sensitivity setting
Frequency Selection	Automatic
Migration Per Minute Its capacity	60 People
Interference	Perimeter signals digitally filtering
Guarantee	2 years

Standard Features

- 6 Zone Multizone feature
- Complete security scan
- High discrimination ability
- The position of one or more metals on the two sided light indicator determination
- Very high detection speed
- High protection against external interference
- High reliability
- 7/24 suitable for uninterrupted operation

Standard Features

- Sensor counting people passing by
- Audible, illuminated and alphanumeric display metal density indicator
- Password to login to programming

Options

- Battery: 8 hours back-up time battery
- Remote control
- Test objects

Suitability

- People with a pacemaker, pregnant women or magnetic storage (USB ,CD...)electronics Does not damage material
- The device complies with EEC 89/336 It has CE, ISO 9001:2008
- High reliability
- 7/24 suitable for uninterrupted operation

Package Sizes

Control Panel	Side Panels
80cm (Length) 52cm (Width)	233cm(Length) 69cm (Width)
33cm (Height)	28cm(Height)