

# PG-555 WP

## Portable Door Frame Metal Detectors

It has the ability to work uninterruptedly for 40 hours with its own battery without the need for existing mains electricity. It has a digital control panel and programmable memory that can be easily used by all personnel working at the device. Thanks to its self testing and automatic calibration feature, the risk of error is minimized. It is a new generation detector with an LCD screen that works with the keypad and the ability to write a warning message to the users on the screen. Calculates the number of people passing through and locates the metal on it. Shows the exact location of metal with LED Bar Graph. LED indicators have 3 separate detection zones and sensitivity level can be adjusted to the desired sensitivity.



Portable Metal Door Detector is produced in such a way that it can be carried, installed and disassembled by one person. It has the feature of using it in indoor and outdoor environments without any problems. It has a high quality waterproof structure. It has IP55 UV protection.

 **PowerGuard**  
X-Ray Sistemleri

### General Features

- Easy setup
- Portable
- Ability to Use in Open and Closed Areas
- Adjustable Volume Control
- Digital
- Automatic Pass Counting
- Complete Security Scan
- High Discrimination Ability
- LED Display
- LCD Panel
- Touch screen
- Writing Warning Message on LCD Panel
- Programmable Memory
- Automatic Information Storage
- Easy-to-Use Control Panel
- LED Bar Graphic Showing Metal Location
- 3 Independent Detection Zones
- From Head to Toe Detection Zone
- Multiple Detectors Working Side by Side
- Adjustable Volume
- Material Not Affected by UV Rays
- Automatic Calibration
- Self-Testing Ability
- Not Harmful to Pregnant and Pacemaker People



### Technical Specifications

Protocol Used	IP V5 UV Protection
External Dimensions	2000mm x 800mm x 570mm
Internal Dimensions	2200mm x 900mm x 810mm
Cover Dimensions	640mm x 940mm x 590mm
Portable Dimensions	940mm x 610mm x 660mm
Operating temperature	-20C +70C
Humidity Level	95%
Operating Voltage	AC: 110V – 220V
Battery	40 Hours Uninterrupted
Total Weight	50 Kg
Alarm	Audible, Visual, Adjustable
Sensibility	Adjustable
Frequency	Automatic
Interference	Digital Filtering
Calibration	Automatic
Test	Automatic
Screen	LCD
Guarantee	2 Years
Protective Case	Optional