



Device Features

Thanks to its medium-sized tunnel size, bond bags, packages, medium-sized suitcases, cargo, handbags, etc. It is possible to view items easily. Thanks to its ergonomic design, it is the perfect solution especially for narrow spaces. SC-6040 Series X-ray Device usage areas It is a particularly preferred model in Hotels, Holding buildings, Governorships, Municipalities, central buildings of other public institutions and organizations, and all Private and Commercial enterprises.

Computer Specs

Monitor	High Definition Color, LCD Equation, 17 inches
Hard Disk	SG 1TB 3.5"
Operating System	Current Operating System
Resolution	1024 x 1280
Hard Disk	SG 1TB 3.5"
Image Storage	500.000 JPEG, BMP
Monitor	17" LCD
UPS	Optional
CD-RW	Optional

Additional Features:

OTP (Operator Training Program)

Remote Access with Built-in Modem

Hazardous substance detection

Audible Warning Feature

General Features

Tunnel Dimensions	614mm X 417.5mm
Speed of Conveyor	0.2 m/s
Conveyor Ground Height	684 mm
Conveyor Load Capacity	150 KG
Resolution	40 AWG Typical
Spatial Resolution Level	Dia 1.0mm
Penetration	32mm-35mm
Object Separation Feature	Organic / Inorganic
Penetration Resolution	40 AWG
Movie Security	ASA/ISO 1600 Film
System Noise	<58db
Weight	455kg
General Dimensions	2007,5mm (length) 868mm (width) 1314mm (height)
Operating temperature	+5C/+40C/%95RH
Storage Temperature	-20C/+60C/95% Humidity
Operating Voltage	AC 220 V 50 Hz
Working Current	1.0 KW (max)

Optional Features:

Smart Sensor

Second Monitor Option and Monitor

Size Selection

Detection of dangerous goods automatic tape stop

Input-Output Roles

Control Console